




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : A61F 2/06	A1	(11) International Publication Number: WO 00/03661 (43) International Publication Date: 27 January 2000 (27.01.00)
(21) International Application Number: PCT/EP99/06108 (22) International Filing Date: 16 July 1999 (16.07.99) (30) Priority Data: 98/09137 17 July 1998 (17.07.98) FR 99/03962 30 March 1999 (30.03.99) FR (71) Applicant (for all designated States except US): B. BRAUN MELSUNGEN AG [DE/DE]; Carl-Braun-Strasse 1, D-34212 Melsungen (DE). (72) Inventors; and (75) Inventors/Applicants (for US only): ROUSSIGNE, Maurice [FR/FR]; 36, rue du Père de la Croix, F-86000 Poitiers (FR). NADAL, Guy [FR/FR]; 8, rue Condorcet, F-86000 Poitiers (FR). (74) Agent: LERNER, François; Cabinet Lerner & Associés, 5, rue Jules Lefebvre, F-75009 Paris (FR).		(81) Designated States: JP, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published With international search report.

(54) Title: EXPANDABLE STENT

(57) Abstract

The invention relates to a stent having a unitary structure and having a principal axis (1a) and a succession of axially aligned tubular stages (10, 20, 30...), at least some of those stages being defined by a regular pattern having consecutive loops (40, 60, ...) closed on themselves, with a succession of hairpin-shaped apices (3, 4, 5, 6, ...) which are connected consecutively, in pairs, by a branch (15, 17, ...), each branch having two inflexion points (15a, 15b, ...) defining a double inflexion region (19), the loops being arranged in phase from one stage to an adjacent stage and being connected to one another by connecting bars (21) linking the apex region of a loop of a given stage to the region (19) of the inflexion points of a loop corresponding to it axially, in a preceding stage or in a following stage, in an alternating manner on the perimeter of said given stage.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

EXPANDABLE STENT

The invention relates to an expandable support for an
5 anatomical lumen (or duct), and in particular for a blood vessel.

Such a support is typically called a stent when it is a
duct expander that is to support the wall of the duct in
10 order to prevent the passage there from being (too) narrow.

The object of the invention is to improve the efficiency
and the tolerance by patients of existing supports. The
15 flexibility and the suppleness of the support have been particularly researched in order to promote its implantation and the following of the natural bends in the duct concerned, in particular if it is a coronary vessel.

20 With regard to implantation, particular attention has also been paid to the ability of the support to be implanted endoluminally (SELDINGER method, in particular) by means of an insertion device having a small diameter.

25 To that end, an important feature of the invention provides that the proposed expandable support (or stent) has a unitary structure and a principal axis and a succession of axially aligned tubular stages, at least
30 some of those stages being defined by a regular pattern having consecutive loops closed on themselves, with a succession of hairpin-shaped apices which are linked consecutively in pairs by a branch, each branch having two inflexion points defining a double inflexion region,

the loops being arranged in phase from one stage to an adjacent stage and being connected to one another by small connecting bars linking the apex region of a loop of a given stage to the region of the inflexion points of a loop corresponding to it axially, in a preceding or
5 following adjacent stage, in an alternating manner on the perimeter of the "given stage" concerned.

Still for the purpose of adapting the flexibility to the bends in the duct, especially if it is a coronary duct,
10 while nevertheless ensuring efficient internal support of the duct, a supplementary feature of the invention recommends that the two inflexion points of each branch define substantially an open "S" so that the branch does
15 not have a curve summit.

Likewise in order to improve the balance between flexibility and resistance to crushing, it is recommendable for the connecting bars to be substantially
20 in a zigzag arrangement, from stage to stage.

Still with the same aim, and also with the aim of ensuring an appropriate size for the cells (defined by the loops and bars), another feature of the invention
25 recommends that the loops of two adjacent stages partially overlap one another.

And, in order to promote a balanced opening of the stent from stage to stage along its axis, yet another feature
30 recommends that, in a given stage, the connecting bars between stages connect the loops of the structure alternately to a preceding adjacent stage or to a following adjacent stage, starting from the linking

branch arranged alternately on one or other side of the central apex of the consecutive loops.

It should also be noted that an important feature of the invention additionally recommends:

- that the double inflexion region be arranged at the median portion of the branch under consideration,
- that, on each side of that region, the branch have a portion, for connection to the corresponding apex,
- 10 which extends substantially parallel to the axis of the stent, in a substantially rectilinear manner,
- that the apices be rounded,
- and that each connecting bar be substantially rectilinear and extend parallel to the axis of the stent
- 15 in order to connect two branches arranged (substantially) in the axial extension one of the other, in two adjacent stages.

Thus, the design of the stent structure is prevented from being overcomplicated while obtaining appropriate dimensions for the cells and a structure "design" conferring on the structure an optimised relationship between flexibility and crushing resistance.

25 The bearing and the positioning conditions of the support, once it is implanted (and therefore radially deployed) in the duct have also been researched because the support must have, at its free ends, a diameter in its deployed state at least equal to that of the

30 remainder of the structure and must be able to stay substantially in its implantation position without necessarily comprising hooks or other means for securing to the duct wall.

It is therefore by relative friction and by its radial bearing force (which is opposed by the radial resistance of the duct wall) that the support holds itself in position.

5

The ability of the support to follow the natural bends in the duct concerned has also been taken into consideration.

10

In order to satisfy those requirements, a solution suggested by the invention consists in particular in proposing a support, the above-mentioned the coaxial stages of which define a substantially cylindrical wall surface having a circular cross-section, the support
15 being characterised in that at least one of said stages, respectively the first and the last, arranged at its proximal and distal free ends, comprises free-end apices having a widened portion along the circumferential wall surface, with at least one component along the perimeter
20 of the structure, in a plane perpendicular to the axis of said structure.

With apices thus widened at the proximal and/or distal free ends of its structure, the support provides a
25 widened surface for bearing against the inner wall of the duct, thus permitting the creation at those end sites of regions of increased resistance to any forces which would tend to displace the support along the duct.

30

In that connection, it has also been noted that it is preferably exclusively along the perimeter of the proximal and/or distal free ends that it is advantageous

to promote (that is to say, increase) the contact area between the support and its receiving duct.

Thus, another feature of the invention provides that the widened portion of the above-mentioned free-end apices is terminated, parallel to the axis of the structure, by a rectilinear portion in a plane substantially perpendicular to said axis.

10 It will be appreciated that the presence of such a "rectilinear portion" also avoids the presence at that site of a shape which could be aggressive with respect to the duct wall.

15 Also in connection with that same consideration, another feature of the invention recommends that the above-mentioned widened apex portions each have a substantially triangular shape with rounded angles.

20 It will be appreciated that such a triangular shape enables a lengthening of the contact surface between the support and the inner wall facing the duct to be reconciled with the constraint of a shape which promotes that contact, in particular along the perimeter of the end stages concerned, without leading to a shape which
25 could traumatise the duct wall.

A more detailed description of the invention will now be provided with reference to the appended drawings in which:
30

- Figure 1 is a general front view of an expandable support according to the invention,
- Figure 2 is an enlarged view of the detail marked II in Figure 1

- Figure 3 shows a "basic" loop (enlarged detail III of Figure 1, without the bar),
- Figure 4 is a general view of another first embodiment of an expandable support according to the invention;
- 5 - Figure 5 is an enlarged local view of the detail marked V in Figure 4;

The structures shown in the enclosed Figures are vessel expanders (in particular coronary vessel expanders),
10 typically called stents.

The form of their fundamental structure as illustrated could, however, be used in other types of anatomical support, such as, for example, prostheses for aneurysm
15 (production of the stent associated with a supple sleeve which channels the blood), or an internal support for a portion of the oesophagus or for a portion of the urethra, for example.

20 The expander 1 represented is in particular usable in the treatment of a stenosis.

The expander is a hollow cylindrical tube, of axis 1a, which may occupy, in particular, two states: a radially
25 confined state as in Figures 1 and 2, and a radially deployed state, which has not been shown.

Typically, its axial length is from 9 mm to 30 mm, while its diameter (in the confined state) may be of the order
30 of from 1.3 to 3 mm, which diameter can increase to 4 or even 6 mm in the radially deployed state.

The support 1 may in particular be manufactured by laser cutting from a thin plate of metal, such as type 316L

stainless steel, of the order of one tenth of a millimetre thick.

5 Manufacture from a material "having heat shape memory", such as "nitinol" (registered trademark) would also be possible.

The result is an open integral structure (in a single piece).

10

Figure 2 shows more clearly the "design" of the structure which, in this particular case, is identical over the entire surface thereof, except for the proximal 1b and distal 1c free ends where, respectively, the first and 15 last stages 10, 100, are found.

Thus, the structure may be described as having a succession of stages, such as those marked 10, 20, 30 in Figure 2, which are all spaced along the axis 1a to form 20 individually an annular cylinder of an individual height of from 1 mm to 1.5 mm.

In this particular case, the diameter of the ring defined at each stage is constant over the entire length of the 25 stent, both in the confined state and in the radially deployed state.

It may be considered that each stage extends along a cylinder portion of axis 1a and that, except for the end 30 stages 10, 100, each of the intermediate stages located between them is defined by a regular pattern having consecutive loops closed on themselves with a succession of apices marked 3, 5, 7, 9, 11, 13, in the case of some of them, in Figure 2.

All those apices located at the axial ends (that is to say, terminating the loops of the stage under consideration along an axis parallel to the axis 1a) will
5 be regarded as being "hairpin-shaped" although each apex is rounded in order to be atraumatic.

In one and the same stage, two successive apices are connected by a linking branch (such as 15 and 17,
10 respectively, for the apices 5-7 and 7-9 of the stage 10, in Figure 2).

Each branch has two inflexion points, such as 15a, 15b and 17a, 17b, which define a double inflexion region, to
15 the extent that they are relatively close to one another, on the branch concerned.

The thus defined loops of the stages are arranged opposite one another from one stage to another, including
20 as regards the first and last stages 10, 100.

Figure 3 shows the design of a "basic" loop of the structure.

25 It will thus be appreciated that each basic loop has a central peak apex, such as that marked 3 in Figure 3, connected to two linking branches 22,24 which have a double inflexion region and which are arranged one on each side of the axis of symmetry 3a. Each branch
30 therefore comprises two portions (such as 22a and 22b in the case of the branch 22). Each portion is preferably (substantially) parallel to the axis 1a (or 3a).

- Advantageously, each double inflexion region, such as 19 in the case of the branch 22, is arranged at the median portion of the branch (approximately at mid-height) and the two inflexion points are close to one another, in such a manner as to define a (short) shoulder which widens the loop at its base until it reaches approximately three times the width (d) of its peak, at the site of its central apex (Figure 2).
- 10 The double inflexion region preferably has the shape of an open "S", that is to say, a concave curve followed by a convex curve, without an intermediate curve summit, thus preventing excessive tortuousness.
- 15 Two successive stages (such as 20 and 30) where the loops are arranged in phase, are connected to one another by small connecting bars 21.

In the Figures, the bars are in a zigzag arrangement, from stage to stage, that is to say that, considering a loop (such as 60) of a given stage, which loop is connected, parallel to the axis 1a, by a bar 21 to the loop corresponding to it in the following adjacent stage 30, the two loops 40, 80 bordering it on each side are each connected by another bar 21 to the loop arranged in their axial continuation, in the preceding stage 10.

With the exception of the two end stages 10, 100 (where the loops are connected only on one side, to a single stage) the loops of all the intermediate stages are therefore connected, per stage, on the perimeter of the structure, alternately to the loop located in their axial extension in the preceding stage or in the following stage.

The "hairpin-shaped" form of the region of the apices 3, 4, 5, 6, 7, ..., will also have been noted, although each apex is rounded in order to be atraumatic.

5

Bearing in mind the above, and in particular the arrangement, without a phase shift, of the loops from one stage to an adjacent stage, the connecting bars 21 may be rectilinear bars which each extend parallel to the axis
10 1a in order to connect the double inflexion region, such as 19, to the apex region (such as 4) of the loop (such as 40) facing it axially. Other forms ("C"-shaped, "<"-shaped, ...) could be provided for. Preferably, however, all the bars will be in the same form.

15

In the embodiment illustrated, it will be appreciated that, in order to balance the structure, the bars 21 of the loops 40 and 60 (this is reproducible over the remainder of the structure) connect the loops under
20 consideration alternately to a "preceding" adjacent stage 10 or to a "following" adjacent stage 30, starting from the linking branch arranged alternately on one and the other side of the axial-end apex considered (such as 4, 14, 6, 16, ...) (see connection at the top to the left
25 of the apex 4 of the loop 40, then at mid-height to the right of the apex 6, at the site of the double inflexion of the loop 60 between the axial-end apices 6 and 16).

The axial length of the bars 21 is also advantageously
30 such that the loops of the two adjacent stages partially overlap axially, preferably over approximately from one to a few tenths of a millimetre (the thickness of the filament of material forming the loops), see height e in Figure 2.

In the embodiment of Figures 4 and 5, each apex of the loops constituting the first and last stages 10', 100' has, at the site of the perimeter of the corresponding free ends 1'b, 1'c, a widened portion 23 which is found nowhere else and, in particular, is not found at the site of the "intermediate" apices, such as those marked 25, 27, 31, 33 in Figure 4 or 5 (substantially "hairpin-shaped" apex).

10

In order to promote the bearing and retaining effect sought in relation to the anatomical duct, each widened portion 23 extends along the circumferential wall surface of the structure 100 considered as a whole, that is to say, the widened portions do not project radially, either towards the inside or towards the outside of the general cylindrical surface of the structure.

In the case in point, each widened portion 23 incorporates a rectilinear "peak" portion 29 (which defines its widened apex region) in a plane substantially perpendicular to the axis 1'a (plane marked by the line 70 in the case of the free end 1'b and by the line 80 in the case of the distal end 1'c, in Figure 4).

25

Bearing in mind the general form adopted for the loops of the structure, Figures 4 and 5 also clearly show that each widened portion of the end apices 23 preferably has a substantially "triangular" shape with rounded angles 32 which is particularly adapted to the "design" as a whole already presented.

As in the case of Figures 1 to 3, the support of Figures 4 and 5 is provided to be radially deployed starting from

the form illustrated in the Figures starting from their illustrated radially confined state, under the effect in particular of an inflatable internal balloon (not shown), or even a thermal effect if the material used is a
5 "material having heat shape memory".

It will be further noted that each stage of the above-mentioned structures develops, while closing on itself (in the manner of a basic ring) in a plane perpendicular
10 to the longitudinal axis of the structure, in such a manner that the structure may be regarded as having a succession of annular stages regularly spaced along said axis. In addition, each stage is defined by a fine strip of looped material having a succession of troughs and
15 peaks.

Further, the use of the above supports 1, 100 is conventional.

20 After placing them around their inflatable balloon (if they do not have a heat shape memory), they are placed in an insertion device and they are introduced into their (coronary) receiving duct inside which they are deployed by inflating the balloon until they bear against the
25 inner wall of the duct (vessel). The introduction system is then withdrawn and the support is left in place.

CLAIMS

1. Expandable support for an anatomical duct, the support having a unitary structure and having a principal axis (1a) and a succession of axially aligned tubular stages (10, 20, 30, ...), at least some of those stages being defined by a regular pattern having consecutive loops (40, 60, ...) closed on themselves, with a succession of hairpin-shaped apices (3, 4, 5, 6, ...) which are linked consecutively in pairs by a branch (15, 17, ...), each branch having two inflexion points (15a, 15b, ...) defining a double inflexion region (19), the loops being arranged in phase from one stage to an adjacent stage and being connected to one another by small connecting bars (21) linking the apex region of a loop of a given stage to the region (19) of the inflexion points of a loop corresponding to it axially, in a preceding or following adjacent stage, in an alternating manner on the perimeter of said stage.

20

2. Support according to claim 1, characterised in that:

- the double inflexion region (19) is arranged at the median portion of the branch under consideration,
- 25 - on each side of that region, the branch has a portion (22a, 22b), for connection to the corresponding apex, which extends substantially parallel to the axis of the support and which is substantially rectilinear,
- the apices (3, 4, ...) are rounded,
- 30 - and each connecting bar (21) is substantially rectilinear and extends parallel to the axis (1a) of the support in order to connect two branches arranged in the axial extension one of the other, in two adjacent stages.

3. Support according to claim 1 or claim 2, characterised in that the two inflexion points of each branch define substantially an open "S", so that the branch does not have a curve summit.

5

4. Support according to any one of the preceding claims, characterised in that the connecting bars (21) are substantially in a zigzag arrangement, from stage to stage.

10

5. Support according to any one of the preceding claims, characterised in that the loops of two adjacent stages (10, 20, 30, ...) partially overlap one another.

15

6. Support according to any one of the preceding claims, characterised in that, in a given stage, the bars (21) connect the loops alternately to a preceding adjacent stage or to a following adjacent stage, starting from the linking branch arranged alternately on one or other side of the central apex (3, 4, 6, 7, 8, 11, ...) of the consecutive loops.

20

7. Support according to anyone of the preceding claims, characterised in that :

25

- the support has along its axis a proximal free end and a distal free end,

- the support also has a succession of tubular stages (10, 20, ...)

- the coaxial stages of the support define a substantially cylindrical wall surface having a circular cross-section, and

30

- at least one of said stages, respectively the first (10, 10') and the last (100, 100') arranged at the proximal and distal free ends, comprises free-end apices

having a widened portion (23) along the circumferential wall surface, with at least one component along the perimeter.

5 8. Support according to claim 7, characterised in that, between two successive free-end apices (23) of the first (10') and/or of the last (100') stages of the structure, the corresponding loop has at least one hairpin-shaped apex (25, 27).

10

 9. Support according to claim 7 or claim 8, characterised in that the widened portion of the free-end apices is terminated, parallel to the axis of the structure, by a rectilinear portion (29) in a plane (70, 15 80) which is substantially perpendicular to said axis.

 10. Support according to claims 7 to 9, characterised in that the widened portion of the free-end apices has a substantially triangular shape having 20 rounded angles (32).




FIG. 1




FIG. 3







FIG. 2

FIG. 4



INTERNATIONAL SEARCH REPORT

Int. Application No.
PCT/EP 99/06108

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 A61F2/06

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 A61F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 806 190 A (SORIN BIOMEDICA CARDIO SPA) 12 November 1997 (1997-11-12) figure 4 figure 9 column 7, line 55 -column 10, line 11 claims 1-6,8 ---	1,2,4, 6-9
A	WO 98 22159 A (BEYAR MORDECHAY ;BEYAR RAFAEL (IL); GLOBERMAN OREN (IL); MEDTRONIC) 28 May 1998 (1998-05-28) figure 2 page 3, line 17 - line 25 claim 11 ---	1-3,7
A	DE 297 08 879 U (JOMED IMPLANTATE GMBH) 31 July 1997 (1997-07-31) figure 2 page 5, line 21 -page 6, line 21 ---	1-3,7
-/--		

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- "&" document member of the same patent family

Date of the actual completion of the international search

21 October 1999

Date of mailing of the international search report

28/10/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl.
Fax: (+31-70) 340-3016

Authorized officer

Mary, C

INTERNATIONAL SEARCH REPORT

Int. App. No.

PCT/EP 99/06108

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DE 297 08 689 U (JOMED IMPLANTATE GMBH) 17 July 1997 (1997-07-17) figure 2 page 5, line 3 - line 15 ---	1,7
A	DE 297 02 671 U (JOMED IMPLANTATE GMBH) 10 April 1997 (1997-04-10) figures 2-5 figure 6 figures 7-10 claim 1 ---	1,7
A,P	US 5 911 754 A (KANESAKA NOZOMU ET AL) 15 June 1999 (1999-06-15) figure 1 ---	1,7-9
A,P	WO 98 40035 A (UNITED STATES SURGICAL CORP) 17 September 1998 (1998-09-17) figures 6,12 page 9, line 28 -page 10, line 4 page 11, line 10 - line 22 -----	1,7,10

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 99/06108

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0806190 A	12-11-1997	IT T0960373 A	10-11-1997
		IT T0960374 A	10-11-1997
		IT T0960375 A	10-11-1997
		IT T0960376 A	10-11-1997
		IT T0960377 A	10-11-1997
WO 9822159 A	28-05-1998	AU 5355598 A	10-06-1998
		EP 0893977 A	03-02-1999
DE 29708879 U	31-07-1997	CA 2237476 A	20-11-1998
		EP 0879584 A	25-11-1998
		JP 10328312 A	15-12-1998
DE 29708689 U	17-07-1997	CA 2237466 A	15-11-1998
		EP 0878174 A	18-11-1998
		JP 10323396 A	08-12-1998
DE 29702671 U	10-04-1997	WO 9835634 A	20-08-1998
		EP 0900063 A	10-03-1999
US 5911754 A	15-06-1999	NONE	
WO 9840035 A	17-09-1998	AU 6464298 A	29-09-1998